

## 29 126 DC0 GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH 3 VALVES



### PRODUCT DESCRIPTION

- Colour: Supersteel
- set for final installation for
- GROHE Rapido SmartBox (35 600/35 604)
- metal wall escutcheon with GROHE FastFixation (covered escutcheon and shaft sealing, covered fixing), retroactively 6° adjustable
- GROHE Long-Life finish
- SmartControl push for ON-OFF, turn for volume adjustment from GROHE Water Saving to Full Flow
- exchangeable symbols
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE SafeStop at 38°C
- GROHE SafeStop Plus optional temperature limiter at 43°C or 46°C included
- built-in non return valves and dirt strainers
- multiple outlets can be run simultaneously
- without roughing-in-set
- flow performance: outlet A = 23 l/min outlet B = 27 l/min outlet C = 23 l/min outlet A + B = 33 l/min outlet A + B + C = 36 l/min

## 29 126 DC0 GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH 3 VALVES



### SPARE PARTS, July 2018 – now

- 1: Mounting plate (Order-nr. 48362000)
  - 2: Temperature control handle (Order-nr. 49029DC0)
  - 3: Escutcheon (Order-nr. 49042DC0)
  - 4: Push button (Order-nr. 48361DC0)
  - 5: Cartridge (Order-nr. 48359000)
  - 5.1: Spindle (Order-nr. 49088000)
  - 6: Thermostatic compact cartridge 3/4" (Order-nr. 49028000)
  - 7: Non-return valves (Order-nr. 47979000)
  - 8: Ball seal dia. 9x6.8 mm (Order-nr. 48360000)
  - 9: Socket spanner (Order-nr. 49059000)\*
  - 10: GROHE TurboStat cartridge 3/4" (Order-nr. 49003000)\*
  - 11: Service stops (Order-nr. 1405300M)\*
  - 12: Universal extension set single-lever mixers, 25 mm (Order-nr. 14048000)\*
- \* Optional accessories